

TECHNICAL DATA

SR-350 VOC COMPLIANT PRIMER REDUCER

January 2011

PRODUCT DESCRIPTION:

SR-350 is a balanced solvent blend designed to thin epoxy primers and maintain VOC compliance of 350 G/L. It can be used to control film thickness per coat, reduce orange peel, improve wetting of topcoat to primer and reduce dry spray or dry spots in painted areas. This product can also be used with electro static and non-electro static equipment. It is most helpful in temperatures from 65 - 95°F.

MEETS OR EXCEEDS THE PERFORMANCE REQUIREMENTS OF SPECIFICATION:

Bombardier BAMS 565-008, Type II / Airbus AIMS 04-04-013 / and Boeing BMS 10-72 Type IX

MIXING / APPLICATION:

After mixing the paint well, the SR-350 solvent reducer should be stirred in thoroughly.

The SR-350 solvent reducer should be added as needed to control application viscosity and flow out. Generally 5% to 20% by volume is found helpful. Excessive amounts will cause inadequate coverage and possibly runs in the paint.

PHYSICAL PROPERTIES:

Appearance:	Clear solvent blend
Density:	7.27 lbs/gallon
Shelf Life:	2 years from date of manufacture

PRECAUTIONS:

Use with adequate ventilation and proper respiratory protection. See MSDS for complete instructions and precautions.