

TECHNICAL DATA

SSS STAIN SERIES SOLVENT SPRAY STAINS

November 2010

This solvent stain system has been designed to provide a brilliant transparent color to any wood substrate by spray application. It penetrates the wood pores to allow for consistent stain color without blotching. There are a variety of stain bases available with dry times to fit any requirement. It is recommended that the stain be allowed to dry two hours before applying insulator or recoating with another product.

These stains can be applied directly to the wood, over a wipe filler, or between the sealer or topcoats. They can also be added directly to the insulator, polyurethane color coat or the polyester sealer to color it and to add even more depth.

Formulations are available that allow the customer to spray and then wipe the stain allowing for better penetration into the wood and also to permit wiping for a uniform color without streaks or overlapping.

Stain concentrates (SCO-Series) are available in a variety of colors to give the customer the ability to custom tint stain colors while using clear bases.

SCO-Series:

SCO-101—Black Stain Concentrate
SCO-201—Brown Stain Concentrate
SCO-301—Yellow Stain Concentrate
SCO-401—Orange Stain Concentrate
SCO-501—Red Stain Concentrate
SCO-502—Bright Red Stain Concentrate
SCO-701—Green Stain Concentrate
SCO-801—Blue Stain Concentrate
SCO-802—Violet Stain Concentrate